

## JIVA-8015/5815/5615 Series SPECIFICATIONS

SPECIFICATIONS	JIVA-8015	JIVA-5815	JIVA-5615
Processor	Celeron 2.0 GHz	C3 1.0 GHz	Eden 667 MHz
Memory	256 MB, DDR 266 (expandable to 2GB)	128 MB, DDR 266 (expandable to 1GB)	
Video memory	16-128 MB shared memory	16-64 MB shared memory	
Display	15" TFT, 1024x768, 250 nits		
Tilt adjustment	From 17.5° to 76.5°		
Touch sensor	PS/2 resistive panel standard (optional anti-scratch IR RS232 interface)		
Touch resolution	1024x1024, mouse emulation		
<b>Expansion</b>			
Hard disk drive	Build-in 3.5", 40GB	Build-in 3.5", 20GB	N/A
FDD	Option for USB interface		
Internal UPS	Yes. (Battery optional)		
Mounting option	Table top or wall mount		
<b>Connectivity</b>			
Audio Line Output	Standard (with 2 speakers)	Standard (Audio Amp + Speakers option)	
VGA Port	1x		
Serial Port	4x		
Parallel Port	1x		
CR Port	1x		
USB Port	2x		
PS/2 KB & MOUSE	YES		
LAN Port	10/100 MHz base Ethernet		
Compact Flash Port	N/A	1 Type II connector (Compact Flash Memory Card is option)	
OS Support	Win 2000/XP Pro/WEPOS	Win NT/2000/CE.NET/WEPOS/XP Pro/Linux	Win CE.NET or Linux LAN Boot(upgradable)
Housing Color	Charcoal		
<b>Physical dimensions</b>			
Dimension	375mm(W) x 282mm(D) x 296-373mm(H) 14.8" x 11.1" x 11.7"-14.7"		
Weight	9.08kg (19.98 lbs, external power adaptor)	8.94kg (19.67 lbs, external power adaptor)	8.34kg (18.35 lbs, external power adaptor)
Electrical requirements	AC adaptor: Input 100-240V, output DC 12V/150W	AC adaptor: Input 100-240V, output DC 12V/80W	AC adaptor: Input 100-240V, output DC 12V/60W
Storage Condition	-20°C ~ +60°C; 10%RH ~ 80%RH; non-condensing; maximum wet bulb 28.9°C		
Operation Condition	0°C ~ +40°C; 20%RH~80%RH; non-condensing; maximum wet bulb 26°C		
Safety Certifications	PSU: ULVDE/T mark Terminal: FCC, CE (class A)		
<b>Option peripherals</b>			
KP-100	Mini footprint design security keyboard, 40 keys(24 programmable keys and ten key configuration) attachment options: MSR 40 keys		
Total Keys	0-9, +, -, =; total 16 keys		
Predefined keys	Win98/2000/XP pro/WEPOS/NT/DOS		
OS support	ASCII or SCAN code		
Code Programmable	1 to 255 characters per key		
Programmable capacity	100 years data retention		
Data Memory	5V/200 mA max. from the PS/2 KB port		
Power Source	ISO 7811 option 2 tracks(1&2 or 2&3), 3 tracks (1,2&3 with software programmable parameter) or JIS II, KB interface		
MSR	Includes: MSR / iButton reader		
SD-100	ISO 7811 option 2 tracks(1&2 or 2&3), 3 tracks (1,2&3) or JIS II		
MSR	Programmed by RS232 interface, output through PS/2 KB or RS232 interface		
iButton Reader	In USB interface, Includes: MSR / Optical finger print sensor		
SD-200	ISO 7811 option 2 tracks(1&2 or 2&3), 3 tracks (1,2&3)		
MSR	Optical type: Detection area: 14.6x18.1 mm / Resolution: 512 dpi x 8 bit gray scale / OS support: Win 98/2000/NT 4.0/XP		
Finger Print Sensor	Bar Code Card Reader, USB interface		
BC-100U	12.1" color LCD TFT as second display with rotatable bracket on rear lower base		
LM-6201	2 by 20 VFD customer pole display mounted on rear lower base		
PD-2501	2 by 20 LCD low profile customer display mounted on rear lower base		
PD-305	2 by 20 LCD customer display mounted at the back of main display top, RS232 interface		
PD-302	2 by 20 LCD customer display mounted at the back of main display top, RS232 interface		

Information and specifications in this catalogue are subject to change without notice.

### Posiflex Incorporated

6, Wu-Chuan Road, Wu-Ku, Taipei Hsien, Taiwan  
TEL: +886.2.2299.1599 (Rep.) FAX: +886.2.2299.1819/1808  
posiflex@posiflex.com.tw www.posiflex.com



2006 V.01

**POSIFLEX**  
Your Success is Our Vision



## Touch Terminal JIVA 8015/5815/5615 Series

State-of-the-Art Scalability for Integrated POS Solutions



## Touch Terminal JIVA 8015/5815/5615 Series


- 15.1" dual backlit LCD panel-TFT active matrix
- ELO Accutouch or infrared Touch Sensor
- Spill-resistant architecture
- Power guard feature with software controlled power switch to prevent accidental shutdown of system
- Integrated UPS functionality protects the system from intermittent power failures
- Auto-boot ROM support (JIVA-5615)
- Preload compact flash memory card with Windows CE.net (JIVA-5615)
- New standard 4-in-1 slim base stand
  - Optional UPS battery
  - Integrated wall mount bracket
  - Rear mount for 2nd display/pole display
  - HDD (secondary for JIVA-5815 and primary for JIVA-8015)



### Features



Integrated 2-in-1 MSR attachment and finger print sensor (SD-200)



Integrated bar-code card reader (BC-100U)



Integrated MSR and 40-Dynakey programmable keyboard attachment (KP-100)



A patented finger release lever "Gear Lock" mechanism easily adjusts the LCD tilt angle from 17.5° to 76.5°



Security lock to prevent unauthorized access to data input/output devices



Interior Wall Mount

### Available peripherals



Cash Drawer (CR Series)



Second display (LM-6201)



Customer display (PD-302)

### Touch Terminal JIVA 8015/5815/5615 Series

Designed for hospitality, retail and vertical markets that require increased performance at the front-end workstation.